


FLOW RANGE: 3 - 10 GPM

OUTLET SIZE: 1" NPT

NOMINAL DIA. 4"



Specifications subject to change without notice.

4" motor standard, 3450 RPM.

Performance conforms to ISO 2548 Annex B @ 2 ft. minimum submergence.



DIMENSIONS & WEIGHTS


Model No.	HP	Motor Size		Discharge Size	Dimensions										Approximate Shipping Wt.	
		In.	CM		A		B		C		D		E		Lbs.	Kg
7S03-8	½	4	10	1" NPT	21.5	54.6	8.8	22.4	12.7	32.3	3.8	9.7	3.9	9.9	27	12.2
7S05-11	½	4	10	1" NPT	24.7	62.7	9.5	24.1	15.2	38.6	3.8	9.7	3.9	9.9	30	13.6
7S07-15	¾	4	10	1" NPT	29.2	74.2	10.7	27.2	18.5	47.0	3.8	9.7	3.9	9.9	33	15.0
7S10-19	1	4	10	1" NPT	33.6	85.3	11.8	30.0	21.8	55.4	3.8	9.7	3.9	9.9	36	16.3
7S15-26	1 ½	4	10	1" NPT	41.2	104.6	13.6	34.5	27.6	70.1	3.8	9.7	3.9	9.9	46	20.9

NOTES: All models suitable for use in 4" (10 cm) wells.
Weights include pump end with motor in lbs.

MATERIALS OF CONSTRUCTION

COMPONENT	SPLINE SHAFT
Check Valve Housing	304 Stainless Steel
Check Valve	304 Stainless Steel
Diffuser Chamber	304 Stainless Steel
Impeller	304 Stainless Steel
Suction Interconnector	304 Stainless Steel
Inlet Screen	304 Stainless Steel
Pump Shaft	304 Stainless Steel
Straps	304 Stainless Steel
Cable Guard	304 Stainless Steel
Priming Inducer	304 Stainless Steel
Coupling	329/420/431 Stainless Steel
Check Valve Seat	NBR/304 Stainless Steel
Top Bearing	PTFE/304 Stainless Steel
Impeller Seal Ring	PTFE
Intermediate Bearings	PTFE

NOTES: Specifications subject to change without notice.
Valox® is a registered trademark of General Electric Co.



Integrated Environmental Technologies, Inc.
 124 Edgewood Drive, Washington, PA 15301
 (800) 270-6052 | FAX: (724) 261-5330
 sales@ietechinc.com | www.ietechinc.com